SMART DIRECT FLOW



Division of Eagle Water Treatment

Immediate filtration, enjoy fresh water anytime!

FEATURES

- Direct flow of pure water.
- No tank of stagnant water.
- Modern and compact design.
- Long life span of filters and membrane.
- Faucet with intelligent display.
- 2:1 low drain ratio.
- Easy installation and DIY maintenance.







Purification technology: 2 stages direct flow RO system

- A Pre-filter:
 Combined sediment filter + carbon fiber
- Multi-function filter:
 High flow RO membrane + post carbon

Flow Rate: 1,7 LPM

Water efficiency / Recovery rate:
Up to 60% (depending on the quality of the water)

Power consumption: 96W. 24V x 4A

Dimensions (inches) D-11.25" W-6.7" H-18.0"













SMART DIRECT FLOW



Division of Eagle Water Treatment

Smart TDS monitoring panel

4 in 1 functions control:

- water quality detection
- RO membrane auto-flush
- filter replacement alarm
- leak sensor



Built-in multi-function filter

- Adopts advanced composite filter technology.
- Quick-change cartridge design and easy pull-up handles; filter replacement is super easy.

Smart faucet design

- Displays water quality in real time.
- Reminds customers to change filters.

INPUT WATER REQUIREMENTS

Inlet temperature (max. / min.): 38 °C / 5 °C

Inlet TDS: < 1000 ppm

Inlet pressure (max. / min.): 4 / 1 bar (400 / 100 KPa)

Max. hardness: 20 °HF



Model FB-PF



Filtration Media
Sediment PP+Carbon fiber

Function Removes s

Removes sediment, rust, suspended solids, chlorine, taste and odor.

Dimensions (inches) 4.35" x 8.0"



Model FB-RO 600

Filtration Media 600GPD RO membrane+ post carbon

Function

Reduces TDS, lead, salt, atrazine, fluoride, nitrates, PFAS, bacteria, etc., and improves the taste of water.

Dimensions (inches) 4.35" x 15.4"



Division of Eagle Water Treatment

Natural Purity Water Treatment Systems
501 Rivière Sud, St-Eustache, Québec J7R 0E1
Tel.: 450-491-0882 or 1-800-363-6365 Fax: 450-491-2098 Email: info@eaglewater.ca
www.eaglewatertreatmentsystems.com